

Flex Lightline, with SMD2216 LEDs, 192LEDs/meter, 10W/meter. Supplied in 5 meters roll .

Can be cut every 3cm.

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Accessories



7811E



7811F

Related items



20030

Physical Specification

Item Group	09 LED Strips & Profiles
Family	IP67 Flex Lightline
Order Code	7811/W
Material	Silicone
Shape	Rectangular
Length	5000mm
Width	10mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	III
Power(Watts)	10W/m
IP Rating	IP67
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Epistar

LED Number

192LEDs/m

F Mark



Illumination Data

Colour Temperature

3000K

Lumen Output

550lm/m

Light Efficiency

55lm/W

CRI

90

Illumination Diagram



Packing Info

Box Length

32cm

Box Width

32cm

Box Height

2,5cm

Box Weight

0,69kg

Pcs/Carton

40


Barcode

5291889055815

HS Code

9405403990

Energy Label



Warranty

3 Years

Weee Directive

Yes
