



Slim Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery



Related items



20030

Physical Specification

Item Group

09 LED Strips & Profiles

Family
Order Code
Shape
Length
Width
Surface Ceiling
Surface Wall
Surface Floor/Ground
Indoor

The Ultra Slim Range 24V
7823/EW
Rectangular
5m
5mm
Yes
Yes
Yes
Yes

Electrical Characteristics

Fitting

Input Type
Input Voltage
Safety Class
Power(Watts)
IP Rating
Light Source
LED Type
LED Brand
LED Number

Constant Voltage
24V DC

9,6W/m
IP20
LED built in
SMD 2216
Refond
140Leds/m

Illumination Data


Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram

2700K
768lm/m
80lm/W
90


Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,18kg
Pcs/Carton	40
Barcode	5291889048794
HS Code	9405409989

Energy Label



Energy Class	F
--------------	---

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes