

09 LED Strips & Profiles>The 9,6W/m 24V SMD2216 140LEDs/m

7829/W



Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions

Cut every 5cm (7-LED segment)

Gallery



Related items



20030

Physical Specification

Item Group

09 LED Strips & Profiles

Family	The 9,6W/m 24V SMD2216 140LEDs/m
Order Code	7829/W
Shape	Rectangular
Length	5000mm
Width	8mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	<u> </u>
Power(Watts)	9,6W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	140LEDs/m
F Mark	F

Illumination Data

Colour Temperature	3000K
Lumen Output	864lm/m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

Packing Info	
Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,18kg
Pcs/Carton	40
Barcode	5291889054528
HS Code	9405409989
Energy Label	
ENERG 7 ONE Light Ltd 7829/W A B C D E F G	

F

5 Years

Yes

Energy Class

Certification & Warranty

Warranty

Weee Directive