




## DOLIX OUT QPAR51

square, matt chrome

The DOLIX low-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



## TECHNICAL DATA

|                         |                        |
|-------------------------|------------------------|
| Item no.:               | 1001172                |
| Socket                  | GU10                   |
| Lamp                    | QPAR51                 |
| Number of sockets       | 1                      |
| Lamps included          | No                     |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Length                  | 8.8 cm                 |
| Width                   | 8.8 cm                 |
| Height                  | 11 cm                  |
| Installation diameter   | 6.8 cm                 |
| Installation depth      | 11 cm                  |
| Net weight              | 0.197 kg               |
| Gross weight            | 0.23 kg                |
| IP Code                 | IP 65                  |
| Safety class            | II                     |
| Impact resistance class | IK02                   |
| Impact resistance       | 0,2 Joule              |
| Assembly                | Recessed               |
| Assembly details        | Ceiling                |
| Wattage                 | 50 W                   |
| Color                   | silver                 |
| BIG WHITE Page          | 713                    |