


## MEDO 60 CW AMBIENT

LED Outdoor surface-mounted wall and ceiling light, TRIAC, black, 3000/4000K

The high quality MEDO AMBIENT supplements the MEDO series, and impresses with its well thought-out new features: Thanks to its homogeneous, indirect upwards light emission, it generates a decorative AMBIENT effect. A practical switch that provides flexibility, and with the MEDO AMBIENT variant is easy to switch between 3000K and 4000K. The MEDO AMBIENT also excels during installation: The base plate is screwed to the wall or the ceiling, then the body is simply attached to the socket using three clips and can be removed in the same way, of course. The ceiling light can be converted into a pendant using a suspension kit, and is therefore also ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



## TECHNICAL DATA

Item no.:	1001886
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1050mA
Height	9.5 cm
Diameter	60 cm
Net weight	4.945 kg
Gross weight	6.635 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Wattage	40 W
Lumen	4720 / 5120 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	black
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C