


## ESKINA SENSOR

Outdoor surface-mounted wall and ceiling light, anthracite, 3000/4000K, IP54, dimmable

A new family in the SLV lighting world! We are providing you with an integrated outdoor lighting solution with the ESKINA family. Regardless of whether it is a floor stand, a wall and ceiling light or a display fitting. You will find the right light for any application. All of the luminaires can be operated with 3000 K or 4000 K. Versions with motion sensors are also available.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1002904                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 350mA                  |
| Height                              | 22.3 cm                |
| Diameter                            | 13.8 cm                |
| Net weight                          | 1.291 kg               |
| Gross weight                        | 1.604 kg               |
| IP Code                             | IP 54                  |
| Safety class                        | I                      |
| Impact resistance class             | IK02                   |
| Impact resistance                   | 0,2 Joule              |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling,Wall           |
| Dimmable                            | Yes                    |
| Dimming technology                  | trailing edge          |
| Number of through-wires             | 20                     |
| Wattage                             | 14.5 W                 |
| Lumen                               | 1000 lm                |
| Colour temperature                  | 3000/4000 Kelvin       |
| Beam angle                          | 95 °                   |
| Color                               | anthracite             |
| CRI                                 | 80                     |