



## SUPROS MOVE

Indoor LED recessed ceiling light white round 3000K  
60° CRI90 3380lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1003310                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 950mA                  |
| Height                              | 17 cm                  |
| Diameter                            | 19.5 cm                |
| Installation diameter               | 18 cm                  |
| Installation depth                  | 11.5 cm                |
| Net weight                          | 1.542 kg               |
| Gross weight                        | 1.697 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | II                     |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Wattage                             | 36 W                   |
| Lumen                               | 3380 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 60 °                   |
| Color                               | white                  |
| CRI                                 | 90                     |
| LXXBXX data                         | L70B50                 |
| Ambient temperature                 | 25 °C                  |
| BIG WHITE Page                      | 387                    |