




## ENOLA ROUND UP/DOWN L

outdoor LED surface-mounted wall light anthracite  
CCT 3000/4000K

The ENOLA SQUARE and ROUND series of puristic luminaires consist of a cylindrical or square aluminium construction, and are equipped with powerful LEDs. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT. Because of the built-in LED driver, the electrical connection of the luminaire is made directly to a 230V mains voltage supply. In order to cover as wide a range of uses as possible, single and double headed wall lights and ceiling lights are available in round and square version in various sizes. This luminaire contains built-in LED lamps.



### TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1003441                |
| Number of different light outlets   | 2                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700mA                  |
| Width                               | 14 cm                  |
| Height                              | 33.2 cm                |
| Depth                               | 19 cm                  |
| Net weight                          | 3.077 kg               |
| Gross weight                        | 3.843 kg               |
| IP Code                             | IP 65                  |
| Safety class                        | I                      |
| Impact resistance class             | IK06                   |
| Impact resistance                   | 0,2 Joule              |
| Assembly                            | Surface                |
| Assembly details                    | Wall, Wall with Acc.   |
| Number of through-wires             | 10                     |
| Wattage                             | 55 W                   |
| Lumen                               | 5400 / 6000 lm         |
| Colour temperature                  | 3000/4000 Kelvin       |
| Beam angle                          | 38 °                   |
| Color                               | anthracite             |
| CRI                                 | 90                     |