


## **GALEN 60 SP**

Indoor single colour LED profile anthracite CCT switch 3000/4000K

Thanks to the integrated mounting bracket and the splash-proof connection cables, the GALEN LED profile can be installed quickly and easily on walls, floors, or ceilings. It is most suitable as a form of lighting for displays and signs. Added to this is the practical CCT switch, which provides added flexibility as it allows the light colour to be adjusted between 3000K (warm white) and 4000K (neutral white) using an external switch. Robustly made and featuring high-performance LEDs, GALEN is perfect for creating effective or functional lighting in the outdoor areas of shops, hotels, restaurants, or in commercial buildings.



## **TECHNICAL DATA**

Item no.:	1003447
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	450mA
Width	60 cm
Height	6.2 cm
Depth	11.3 cm
Net weight	1.703 kg
Gross weight	1.849 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK03
Impact resistance	0,35 Joule
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Number of through-wires	12
Wattage	18 W
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
	·