


NUMINOS® DLS

Indoor LED recessed ceiling light black/black 3000K 55° gimballed, rotating and pivoting, including leaf springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 690 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| Item no.: | 1003799 |
|--|---------------|
| Number of different light outlets | 1 |
| Secondary power / secondary volta- ge | 250mA |
| Height | 5.2 cm |
| Diameter | 8 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 5.5 cm |
| Net weight | 0.16 kg |
| Gross weight | 0.185 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 8.6 W |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 22 |
| | |