<u>elights</u>






NUMINOS® DLS

Indoor LED recessed ceiling light white/white 3000K 55° gimballed, rotating and pivoting, including leaf springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DLS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 8.6 watts, a luminous flux of 730 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

	003812
Number of different light outlets 1	
Secondary power / secondary voltage	50mA
Height 5.	.2 cm
Diameter 8	cm
Installation diameter 6.	.8 cm
Installation depth 5.	.5 cm
Net weight 0.	.168 kg
Gross weight 0.	.195 kg
IP Code IF	P 20 / IP 44
Safety class	l
Impact resistance class	(02
Impact resistance 0,	,2 Joule
Assembly R	Recessed
Assembly details C	Ceiling
Wattage 8.	.6 W
Lumen 73	30 lm
Colour temperature 30	000 Kelvin
Beam angle 5	5 °
Color	hite
CRI 90	0
UGR≤ 22	2