


NUMINOS® DLL

Indoor LED recessed ceiling light white/white 4000K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2450 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Number of different light outlets 1 Secondary power / secondary voltage 700	mA
	mA
90	
Height 8.5	cm
Diameter 13 c	cm
Installation diameter 11.7	7 cm
Installation depth 9 cr	m
Net weight 0.46	65 kg
Gross weight 0.52	25 kg
IP Code IP 2	0 / IP 44
Safety class III	
Impact resistance class IK02	2
Impact resistance 0,2	Joule
Assembly Rec	ressed
Assembly details Ceil	ing
Wattage 25.4	41 W
Lumen 245	0 lm
Colour temperature 400	0 Kelvin
Beam angle 55 °	
Color whit	te
CRI 90	
UGR≤ 22	