


## **NUMINOS® CL PHASE S**

Indoor LED surface ceiling light white/black 3000K 24  $^{\circ}$ 

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1004134
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	250mA
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.58 kg
Gross weight	0.87 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR≤	13
LXXBXX data	L80B50
BIG WHITE Page	80