


## NUMINOS® PD PHASE S

Indoor LED pendant light white/black 3000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® PD PHASE S pendant light, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.:	1004160
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250mA
Pendant length	250 cm
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.689 kg
Gross weight	0.924 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	10.42 W
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50
BIG WHITE Page	88