


## NUMINOS® PD PHASE S

Indoor LED pendant light white/black 4000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® PD PHASE S, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|  |                            |
|--|----------------------------|
| Item no.:  | 1004166                    |
| Primary nominal voltage                          | 220-240V ~50/60Hz mA/V     |
| Secondary power / secondary voltage <sup>e</sup> | 250mA                      |
| Pendant length                                   | 250 cm                     |
| Height   | 16.2 cm                    |
| Diameter   | 6.5 cm                     |
| Net weight                                       | 0.691 kg                   |
| Gross weight                                     | 0.923 kg                   |
| Safety class                                     | I                          |
| Assembly   | Surface                    |
| Assembly details                                 | Ceiling, Ceiling with Acc. |
| Dimmable   | Yes                        |
| Dimming technology                               | trailing edge              |
| Wattage  | 10.42 W                    |
| Lumen  | 1100 lm                    |
| Colour temperature                               | 4000 Kelvin                |
| Beam angle                                       | 24 °                       |
| Color  | white                      |
| CRI  | 90                         |
| UGR ≤  | 16                         |
| LXXBXX data                                      | L80B50                     |
| BIG WHITE Page                                   | 88                         |