




NUMINOS® CL PHASE M

Indoor LED surface ceiling light white/black 3000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1004232
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage ^e	500mA
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1880 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
BIG WHITE Page	82