<u>elights</u>






NUMINOS® PD PHASE M

Indoor LED pendant light black/black 3000K 36°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® PD PHASE M pendant light, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light has a power consumption of 20.1 watts, a luminous flux of 1970 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004255
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	500mA
Pendant length	250 cm
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.966 kg
Gross weight	1.219 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1970 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR≤	13
LXXBXX data	L80B50
BIG WHITE Page	90