


NUMINOS® PD PHASE M

Indoor LED pendant light white/black 3000K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® PD PHASE M, which impresses as a pendant light with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004256
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage ^e	500mA
Pendant length	250 cm
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.932 kg
Gross weight	1.187 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1880 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
BIG WHITE Page	90