




NUMINOS® PD PHASE M

Indoor LED pendant light black/black 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® PD PHASE M, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1004260
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Pendant length	250 cm
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.955 kg
Gross weight	1.202 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	2060 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L80B50
BIG WHITE Page	90