## <u>elights</u>






## 3~ NUMINOS® PHASE L

3 phase system light whitek/black 4000K  $24^{\circ}$ 

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the 3~ NU-MINOS® PHASE L 3-phase system light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2675 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



## **TECHNICAL DATA**

Item no.:	1004286
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.07 kg
Gross weight	1.4 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2675 lm
Colour temperature	4000 Kelvin
Beam angle	24°
Color	white
CRI	90
UGR≤	19
LXXBXX data	L80B50
BIG WHITE Page	66