




NUMINOS® PD PHASE L

Indoor LED recessed ceiling light black/black 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1004346
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.208 kg
Gross weight	1.502 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2430 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B50
BIG WHITE Page	92