




## NUMINOS® PD PHASE L

Indoor LED recessed ceiling light black/black 4000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® PD PHASE L, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light has a power consumption of 28 watts, a luminous flux of 2620 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1004355
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.2 kg
Gross weight	1.284 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2620 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
BIG WHITE Page	92