


## **NUMINOS® PD DALI M**

## Indoor LED pendant light white/black 4000K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® PD DALI M, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1004552
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	500mA
Pendant length	250 cm
Height	18.5 cm
Diameter	8.5 cm
Net weight	1.08 kg
Gross weight	1.156 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	DALI
Wattage	20.1 W
Lumen	2060 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR≤	25
LXXBXX data	L80B50
BIG WHITE Page	90