


## **NUMINOS® PD DALIL**

Indoor LED pendant light black/black 3000K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® PD DALI L, which impresses as a pendant light with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



## **TECHNICAL DATA**

Item no.:	1004634
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.45 kg
Gross weight	1.753 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	DALI
Wattage	28 W
Lumen	2430 lm
Colour temperature	3000 Kelvin
Beam angle	24°
Color	black
CRI	90
UGR≤	13
LXXBXX data	L80B50
BIG WHITE Page	92