


NUMINOS® PD DALIL

Indoor LED pendant light black/black 3000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® PD DALI L pendant light, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light has a power consumption of 28 watts, a luminous flux of 2400 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMI-NOS ® from SLV?



TECHNICAL DATA

Item no.:	1004636
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.465 kg
Gross weight	1.776 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.
Dimmable	Yes
Dimming technology	DALI
Wattage	28 W
Lumen	2400 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR≤	22
LXXBXX data	L80B50
BIG WHITE Page	92