


MILANDOS 6

white recessed ceiling light, 3000K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With its simple design, the square recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. With a UGR of 23, it conjures up a high-quality, glare-free light. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

Item no.:	1005418
Secondary power / secondary volta- ge	700mA
Length	19.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	19 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.323 kg
Gross weight	0.383 kg
IP Code	IP 20
Safety class	III
Safety class Impact resistance class	III IK02
	···
Impact resistance class	IK02
Impact resistance class Assembly	IK02 Recessed
Impact resistance class Assembly Assembly details	IK02 Recessed Ceiling
Impact resistance class Assembly Assembly details Lumen	IK02 Recessed Ceiling 980 Im
Impact resistance class Assembly Assembly details Lumen Colour temperature	IK02 Recessed Ceiling 980 Im 3000 Kelvin
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle	IK02 Recessed Celling 980 Im 3000 Kelvin 45 °
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color	IK02 Recessed Celling 980 Im 3000 Kelvin 45 ° white
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color CRI	IK02 Recessed Celling 980 Im 3000 Kelvin 45 ° white