


## MILANDOS 8

black recessed ceiling light, 2700K  $45^{\circ}$ 

The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With its simple design, the square recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. With a UGR of 16, it conjures up a high-quality, glare-free light. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



## **TECHNICAL DATA**

Item no.:	1005423
Secondary power / secondary volta- ge	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	III
Safety class Impact resistance class	III IK02
Impact resistance class	IK02
Impact resistance class Assembly	IK02 Recessed
Impact resistance class Assembly Assembly details	IK02 Recessed Ceiling
Impact resistance class  Assembly  Assembly details  Lumen	IK02 Recessed Ceiling 1030 Im
Impact resistance class  Assembly  Assembly details  Lumen  Colour temperature	IK02 Recessed Ceiling 1030 lm 2700 Kelvin
Impact resistance class  Assembly  Assembly details  Lumen  Colour temperature  Beam angle	IK02 Recessed Ceiling 1030 lm 2700 Kelvin 45 °
Impact resistance class  Assembly  Assembly details  Lumen  Colour temperature  Beam angle  Color	IK02 Recessed Celling 1030 Im 2700 Kelvin 45 ° black
Impact resistance class  Assembly  Assembly details  Lumen  Colour temperature  Beam angle  Color  CRI	IK02 Recessed Celling 1030 Im 2700 Kelvin 45 ° black