


MILANDOS 8

black recessed ceiling light, 3000K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The true-to-life colour reproduction index of over 90 and the long LED lifespan of 60,000 hours also speak for the light. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.:	1005424
Secondary power / secondary volta- ge	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	III
Safety class Impact resistance class	III IK02
	···
Impact resistance class	IK02
Impact resistance class Assembly	IK02 Recessed
Impact resistance class Assembly Assembly details	IK02 Recessed Ceiling
Impact resistance class Assembly Assembly details Lumen	IK02 Recessed Celling 1040 lm
Impact resistance class Assembly Assembly details Lumen Colour temperature	IK02 Recessed Ceiling 1040 lm 3000 Kelvin
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle	IK02 Recessed Celling 1040 lm 3000 Kelvin 45 °
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color	IK02 Recessed Celling 1040 Im 3000 Kelvin 45 ° black
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color CRI	IK02 Recessed Celling 1040 Im 3000 Kelvin 45 ° black