


## ESKINA FRAME 125 Pole double

anthracite free-standing lamp, 27W 3000/4000K 95°

An all-round successful design with an elegant rectangular aluminium frame: the popular outdoor lights of the ESKINA family now offer even greater scope for application in the FRAME design alternative. The anthracite-coloured ESKINA FRAME makes a stylish impression in any outdoor area. The pivoting light heads ensure flexible light emission. Thanks to a high IP protection rating, ESKINA is perfectly protected from the elements. In addition, the light colour (3000/4000K) can be selected using the CCT switch before installation. This means that easy installation is a mere formality.



### TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1005439                |
| Number of different light outlets   | 2                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700mA                  |
| Length                              | 11.5 cm                |
| Width                               | 7.3 cm                 |
| Height                              | 125 cm                 |
| Net weight                          | 5 kg                   |
| Gross weight                        | 5.35 kg                |
| IP Code                             | IP 65                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ground                 |
| Wattage                             | 27 W                   |
| Lumen                               | 2200 / 2400 lm         |
| Colour temperature                  | 3000/4000 Kelvin       |
| Beam angle                          | 95 °                   |
| Color                               | anthracite             |
| CRI                                 | 80                     |
| LXXBXX data                         | L70B50                 |
| Minimum ambient temperature         | -20 °C                 |
| Maximum ambient temperature         | 35 °C                  |