<u>elights</u>







HELIA 60

pendant, LED, 3000K, round, white, flat canopy for recessed installation, 7.5W $\,$

With the HELIA 60 you have a recessed pendant with a puristic and clear design. This luminaire is available in black, white and brushed copper. With integrated 7.5 W warm-white premium LED. The luminaire is supplied with a 1.5 m connection lead / suspension. A separate 500mA constant current driver is required for operation.





TECHNICAL DATA

Item no.:	158401
Number of different light outlets	1
Secondary power / secondary volta- ge	500mA
Length	60 cm
Pendant length	150 cm
Diameter	3 cm
Installation diameter	6.8 cm
Installation depth	3 cm
Net weight	0.496 kg
Gross weight	0.748 kg
IP Code	IP 20
Safety class	III
Safety class Assembly	III Recessed
Assembly	Recessed
Assembly details	Recessed Celling
Assembly Assembly details Wattage	Recessed Celling 7.5 W
Assembly Assembly details Wattage Lumen	Recessed Ceiling 7.5 W 550 Im
Assembly Assembly details Wattage Lumen Colour temperature	Recessed Ceiling 7.5 W 550 Im 3000 Kelvin
Assembly Assembly details Wattage Lumen Colour temperature Beam angle	Recessed Ceiling 7.5 W 550 Im 3000 Kelvin 40 °
Assembly Assembly details Wattage Lumen Colour temperature Beam angle Color	Recessed Ceiling 7.5 W 550 Im 3000 Kelvin 40 ° white
Assembly Assembly details Wattage Lumen Colour temperature Beam angle Color	Recessed Ceiling 7.5 W 550 Im 3000 Kelvin 40 ° white