

# 02 Recessed Spots Fixed LED>The 8W Range

# 10108D/BS/W



8W COB LED Dark light recessed Spot.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads









### Dimensions



#### **Physical Specification**


Item Group	02 Recessed Spots Fixed LED
Family	The 8W Range
Order Code	10108D/BS/W
Colour	Brass
Material	Die Cast
Shape	Circular
Height	70mm
Diameter	88mm
Cutout Hole Diameter	73mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes

## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	24V
Safety Class	
Power(Watts)	7,2W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,75-15,2W
Power Factor	0,9
Constant Current	Yes
300mA	14-24
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload
Ilumination Data	
Colour Temperature	3000K
·	
Lumen Output	600lm
Lumen Output	600lm
Lumen Output Light Efficiency	600lm 75lm/W 80 36°
Lumen Output Light Efficiency CRI	600lm 75lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle	600lm 75lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	600lm 75lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	600lm 75lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	600lm 75lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	600lm 75lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	600lm  75lm/W  80  36°  Yes
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length	600lm 75lm/W 80 36° Yes
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width	600lm 75lm/W 80 36° Yes  10,5cm
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width  Box Height	600lm 75lm/W 80 36° Yes  10,5cm 10,5cm 8,5cm
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	600lm  75lm/W  80  36°  Yes  10,5cm  10,5cm  8,5cm

## Energy Label



Warranty	3 Years
Weee Directive	Yes