

## 02 Recessed Spots Fixed LED>The 8W Range

# 10108R/B/W



8W COB LED recessed Spot.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



#### **Physical Specification**

| Item Group           | 02 Recessed Spots Fixed LED |
|----------------------|-----------------------------|
| Family               | The 8W Range                |
| Order Code           | 10108R/B/W                  |
| Colour               | Black                       |
| Material             | Die Cast                    |
| Shape                | Circular                    |
| Height               | 50mm                        |
| Diameter             | 81mm                        |
| Cutout Hole Diameter | 68mm                        |
| Recessed Ceiling     | Yes                         |
| Depth Required       | 50mm                        |
| Indoor               | Yes                         |

### Electrical Characteristics

| Gear   | External-Included                       |
|--|---|
|  |   |
| Fitting + Driver   |   |
| Input Voltage  | 220-240V                                |
| 50 Hz  | Yes                                     |
| 60 Hz  | Yes                                     |
| Safety Class   |   |
| Power(Watts)   | 8W                                      |
| IP Rating  | IP20                                    |
| Light Source   | LED built in                            |
| Dimmable   | No                                      |
| F Mark   | F                                       |
|  |   |
| Fitting  |   |
| Input Type   | Constant Current                        |
| Input Current  | 350mA                                   |
| Voltage  | 20V                                     |
|  | 20 V                                    |
| Safety Class   | ZOV III                                 |
| Safety Class Power(Watts)  |   |
|  |   |
| Power(Watts)   | TIII > 7W                               |
| Power(Watts)  IP Rating  | 7W IP20                                 |
| Power(Watts)  IP Rating  Light Source                                    | 7W IP20 LED built in                    |
| Power(Watts)  IP Rating  Light Source  LED Type                          | 7W IP20 LED built in COB                |
| Power(Watts)  IP Rating  Light Source  LED Type  LED Brand               | 7W IP20 LED built in COB                |
| Power(Watts)  IP Rating  Light Source  LED Type  LED Brand               | 7W IP20 LED built in COB                |
| Power(Watts)  IP Rating  Light Source  LED Type  LED Brand  F Mark       | 7W IP20 LED built in COB                |
| Power(Watts)  IP Rating  Light Source  LED Type  LED Brand  F Mark  Gear | TIII  7W  IP20  LED built in  COB  Cree |

| 50 Hz   | Yes                        |
|---|----------------------------|
| 60 Hz   | Yes                        |
| Power(Watts)  | 5-8,4W                     |
| Power Factor  | 0,9                        |
| Constant Current  | Yes                        |
| 350mA   | 14-24V                     |
| IP Rating   | IP20                       |
| Safety Class  |                            |
| Dimmable  | No                         |
| Housing Material  | Plastic                    |
| Output Terminal   | Cable                      |
| Brand   | Lifud                      |
| Protection  | Short Circuit and Overload |
|   |                            |
| Illumination Data  Colour Temperature   | 3000K                      |
| Illumination Data  Colour Temperature  Lumen Output   | 3000K<br>560lm             |
| Colour Temperature  |                            |
| Colour Temperature  Lumen Output  | 560lm                      |
| Colour Temperature  Lumen Output  Light Efficiency  | 560lm<br>70lm/W            |
| Colour Temperature  Lumen Output  Light Efficiency  CRI   | 560lm<br>70lm/W<br>80      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle   | 560lm<br>70lm/W<br>80      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle   | 560lm<br>70lm/W<br>80      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                           | 560lm<br>70lm/W<br>80      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                           | 560lm 70lm/W 80 60°        |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Pcs/Carton | 560lm 70lm/W 80 60°        |

| Warranty       | 3 Years |
|----------------|---------|
| Weee Directive | Yes     |

Certification & Warranty