

# 02 Recessed Spots Fixed LED>The 8W Range

# 10108R/W/W



8W COB LED recessed Spot.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










### Dimensions



#### **Physical Specification**


Item Group	02 Recessed Spots Fixed LED
Family	The 8W Range
Order Code	10108R/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	50mm
Diameter	81mm
Cutout Hole Diameter	68mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes

## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	17,1V
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Cree
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	5-8,4W
Power Factor	0,9
Constant Current	Yes
350mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload
Ilumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	750lm
Colour Temperature  Lumen Output	750lm
Colour Temperature  Lumen Output  Light Efficiency	750lm 93,75lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	750lm 93,75lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	750lm 93,75lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	750lm 93,75lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	750lm 93,75lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	750lm 93,75lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	750lm 93,75lm/W 80 60°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	750lm 93,75lm/W 80 60°  50

Energy Label



Certification & Warranty		

Warranty	3 Years
Weee Directive	Yes