

9W Dark Light LED Downlight .

Supplied with 300mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

| | |
|------------|--------------------------|
| Item Group | 06 Downlights Fixed LED |
| Family | The SMD Dark Light Range |
| Order Code | 10109D/B/C |
| Colour | Black |
| Material | Die Cast |
| Shape | Circular |
| Height | 50mm |

| | |
|----------------------|-------|
| Diameter | 120mm |
| Cutout Hole Diameter | 110mm |
| Recessed Ceiling | Yes |
| Depth Required | 70mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

| Gear | External-Included |
|------------------|---|
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 9W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

| Fitting | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 300mA |
| Voltage | 28V |
| Safety Class |  |
| Power(Watts) | 8,1W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |

LED Brand

Sanan

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

7,5-12,6W

Power Factor

0,9

Constant Current

Yes

300mA

25-42V

IP Rating

IP20

Safety Class



Dimmable

No

Ambient Temp

-30? ~ +50?

Housing Material

Plastic

Brand

Lifud

Illumination Data

Colour Temperature

4000K

Lumen Output

765lm

Light Efficiency

85lm/W

CRI

80

Beam Angle

100°

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length

15cm

Box Width

7cm

| | |
|------------|---------------|
| Box Height | 13cm |
| Pcs/Carton | 50 |
| Barcode | 5291889060697 |
| HS Code | 9405409900 |

Certification & Warranty

| | |
|----------------|---------|
| Warranty | 2 Years |
| Weee Directive | Yes |