

06 Downlights Fixed LED>The Dark Light Project Range

10110TD/W/W



10W LED recessed downlight, IP54. Suitable for Indoor/Outdoor installation.

Complete with 250mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Dark Light Project Range
Order Code	10110TD/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	67mm
Diameter	115mm
Cutout Hole Diameter	95mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes

Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	39V
Safety Class	
Power(Watts)	9W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage		
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	7-9,2W	
Power Factor	0,9	
Constant Current	Yes	
Output	250mA	
Voltage Range	30-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	ONE	
umination Data		
umination Data		
	3000K	
Colour Temperature	3000K	
Colour Temperature Lumen Output	950lm	
Colour Temperature Lumen Output Light Efficiency	950lm 95lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	950lm 95lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	950lm 95lm/W 80 60°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light acking Info	950lm 95lm/W 80 60° Yes	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light acking Info Box Length	950lm 95lm/W 80 60° Yes	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light acking Info Box Length Box Width	950lm 95lm/W 80 60° Yes 14cm	

Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes