

02 Recessed Spots Fixed LED>The Trimless Mini Range Aluminium

10112BTR/W/W



12W COB LED 2-Step trimless Recessed spot, IP20, for general application. Requires 700mA constant current driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89015A

## Related items



89015AT

## Physical Specification


|                           |                                   |
|---------------------------|-----------------------------------|
| Item Group                | 02 Recessed Spots Fixed LED       |
| Family                    | The Trimless Mini Range Aluminium |
| Order Code                | 10112BTR/W/W                      |
| Colour                    | White                             |
| Material                  | Aluminium                         |
| Shape                     | Circular                          |
| Height                    | 92mm                              |
| Diameter                  | 64mm                              |
| Cutout Hole Diameter      | 70mm                              |
| Recessed trimless ceiling | Yes                               |
| Depth Required            | 110mm                             |
| Indoor                    | Yes                               |
| Adjustable                | No                                |

## Electrical Characteristics

### Fitting

|               |                  |
|---------------|------------------|
| Input Type    | Constant Current |
| Input Current | 700mA            |
| Safety Class  | III              |
| Power(Watts)  | 12W              |
| IP Rating     | IP20             |
| Light Source  | LED built in     |
| LED Type      | COB              |

|              |
|--------------|
| LED Brand    |
| Cable Length |
| F Mark       |

|   |
|---|
| Bridgelux   |
| 40cm  |
|  |

#### Illumination Data

|                      |
|----------------------|
| Colour Temperature   |
| Lumen Output         |
| Light Efficiency     |
| CRI                  |
| Beam Angle           |
| Illumination Diagram |
| Dark Light           |

|  |
|--|
| 3000K  |
| 1100lm   |
| 91,67lm/W  |
| 90   |
| 40°  |
|  |
| Yes  |

#### Packing Info

|            |
|------------|
| Pcs/Carton |
| Barcode    |
| HS Code    |

|               |
|---------------|
| 48            |
| 5291889070054 |
| 9405409900    |

#### Certification & Warranty

|                |
|----------------|
| Warranty       |
| Weee Directive |

|         |
|---------|
| 5 Years |
| Yes     |