

02 Recessed Spots Fixed LED>The COB Dark Light Range Interchangeable

10112L/W/W

Reflector



12W Dark Light COB LED recessed spot with interchargeable reflector.

Reflector must be ordered separately.

Requires 700mA driver.

10112LR/C

Complies with standard EN60598-1 and any other specific standards.















Downloads









Dimensions





96mm

Must be ordered separately



10112LR/B



10112LR/W





89015A



10112LR/CU



10112LR/G

Related items



89015AT

Physical Specification

| Item Group | 02 Recessed Spots Fixed LED |
|----------------------|--|
| Family | The COB Dark Light Range Interchangeable Reflector |
| Order Code | 10112L/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Circular |
| Height | 96mm |
| Diameter | 85mm |
| Cutout Hole Diameter | 75mm |
| Recessed Ceiling | Yes |
| Depth Required | 100mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics


| Fitting | |
|---------------|------------------|
| Input Type | Constant Current |
| Input Current | 700mA |
| Safety Class | |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| | |

| LED Brand | Epistar |
|--------------|---------|
| LED Number | 1 |
| Cable Length | 40cm |
| F Mark | F |
| | |

| Illumination Data | |
|----------------------|-----------|
| Colour Temperature | 3000K |
| Lumen Output | 1100lm |
| Light Efficiency | 91,67lm/W |
| CRI | 80 |
| Beam Angle | 40° |
| Illumination Diagram | |
| Dark Light | Yes |

| Packing info | |
|--------------|---------------|
| | |
| Box Length | 9cm |
| Box Width | 9cm |
| Box Height | 11cm |
| Box Weight | 0,299kg |
| Pcs/Carton | 50 |
| Barcode | 5291889048626 |
| HS Code | 9405409900 |
| | |

Energy Label



| Warranty | 2 Years |
|----------------|---------|
| Weee Directive | Yes |

Certification & Warranty