

## 06 Downlights Fixed LED>The Dark Light Project Range

## 10125TD/W/C



25W LED recessed downlight, IP54. Suitable for Indoor/Outdoor installation.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



## **Physical Specification**

Item Group	06 Downlights Fixed LED
Family	The Dark Light Project Range
Order Code	10125TD/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	235mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	140mm
Indoor	Yes

Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	39V
Safety Class	ŢIII >
Power(Watts)	23,4W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-24W
Power Factor	0,9
Constant Current	Yes
600mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	ONE
Ilumination Data	
Colour Temperature	4000K
Lumen Output	2400lm
Light Efficiency	95lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	25cm
Box Width	25cm
Box Height	10,8cm
Pcs/Carton	12
Barcode	5291889069690
HS Code	9405409900

Warranty	2 Years
Weee Directive	Yes

Certification & Warranty