

06 Downlights Fixed LED>Dark Light Downlights Aluminium

10130A/W/W



30W COB LED recessed downlight, IP20.

Complete with 350mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	06 Downlights Fixed LED
Family	Dark Light Downlights Aluminium
Order Code	10130A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	230mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	170mm
Indoor	Yes

Adjustable

No

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

30W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

350mA

Voltage

84V

Safety Class



Power(Watts)

29,4W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD

LED Brand

LG

LED Number

50


F Mark




Gear

Gear Type

Led Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	20-30,1W
Power Factor	0,9
Constant Current	Yes
350mA	57-86v
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

#### Illumination Data

Colour Temperature	3000K
Lumen Output	2300lm
Light Efficiency	76,67lm/W
CRI	80
Beam Angle	80°
Illumination Diagram	
Dark Light	Yes

#### Packing Info

Box Length	25cm
Box Width	25cm
Box Height	12,5cm
Box Weight	1,5kg

Pcs/Carton

5


Barcode

5291889034193

HS Code

9405409900

## Energy Label



## Certification & Warranty

Warranty

2 Years

Weee Directive

Yes