

06 Downlights Fixed LED>Dark Light Pro Range Aluminium

10130ED/W/B/W



30W COB LED recessed downlight, for general lighting applications.

Complete with 750mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	170mm 100mm

Physical Specification

Item Group	06 Downlights Fixed LED
Family	Dark Light Pro Range Aluminium
Order Code	10130ED/W/B/W
Colour	White-Black
Material	Aluminium
Shape	Circular
Height	100mm

Diameter	170mm
Cutout Hole Diameter	145mm
Recessed Ceiling	Yes
Depth Required	130mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	34,5V
Safety Class	
Power(Watts)	29,3W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835

Sanan
1
F
Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	19-31,5W
Power Factor	0,9
Constant Current	Yes
750mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	LIFUD


Illumination Data

Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	60lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Width	12cm
Box Height	18cm
Pcs/Carton	20
Barcode	5291889058670
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes