

04 Recessed Spots Adjustable LED>The 1W/2W Mini Series Aluminium

11103B/B/W



1W/2W COB LED adjustable recessed spot IP20.

Requires 350mA/700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89004



89004A



89004AT



89004T



Physical Specification

| | |
|------------|----------------------------------|
| Item Group | 04 Recessed Spots Adjustable LED |
| Family | The 1W/2W Mini Series Aluminium |
| Order Code | 11103B/B/W |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |


| | |
|----------------------|-------------|
| Height | 36mm |
| Diameter | 52mm |
| Cutout Hole Diameter | 45mm |
| Recessed Ceiling | Yes |
| Depth Required | 60mm |
| Indoor | Yes |
| Adjustable | 1 Direction |

Electrical Characteristics

Fitting

| | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 350mA/700mA |
| Safety Class |  |
| Power(Watts) | 1W/2W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Bridgelux |
| LED Number | 1 |
| Cable Length | 40cm |
| F Mark |  |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 200lm@700mA |
| Light Efficiency | 100lm/W |
| CRI | 90 |
| Beam Angle | 40° |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Length | 9cm |
| Box Width | 6cm |
| Box Height | 5,5cm |
| Box Weight | 0,080kg |
| Pcs/Carton | 100 |
| Barcode | 5291889042488 |
| HS Code | 9405409900 |

Certification & Warranty

| | |
|----------------|---------|
| Warranty | 5 Years |
| Weee Directive | Yes |