





11107DA/W/W




Diameter	80mm
Cutout Hole Diameter	70mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	1 Direction


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	11V
Safety Class	
Power(Watts)	5,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Cree

LED Number	1
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4-5,5W
Power Factor	0,5
Constant Current	Yes
500mA	8-11V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	600lm
Light Efficiency	85,71lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	10,5cm
Box Width	10,5cm

Box Height	6cm
Box Weight	0,251Kg
Pcs/Carton	50
Barcode	5291889051442
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes