

08 Downlights Adjustable LED>The COB Shop Downlights Pro Die cast

11125B/W/C



25W COB LED Recessed adjustable downlight, shop range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Gallery



Physical Specification


Item Group	08 Downlights Adjustable LED
Family	The COB Shop Downlights Pro Die cast
Order Code	11125B/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	83mm

Diameter	205mm
Cutout Hole Diameter	190mm
Recessed Ceiling	Yes
Depth Required	120mm
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	35V
Safety Class	
Power(Watts)	24,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ

LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	19,6-30W
Power Factor	0,9
Constant Current	Yes
700mA	28-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 2450lm
Colour Temperature	
Colour Temperature Lumen Output	2450lm
Colour Temperature Lumen Output Light Efficiency	2450lm 98lm/W
Colour Temperature Lumen Output Light Efficiency CRI	2450lm 98lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2450lm 98lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2450lm 98lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2450lm 98lm/VV 80 35°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	2450lm 98lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2450lm 98lm/VV 80 35°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	2450lm 98lm/W 80 35° 23,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	2450lm 98lm/W 80 35° 23,5cm 23cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	2450lm 98lm/W 80 35° 23,5cm 23cm

Barcode	5291889039372
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes