

08 Downlights Adjustable LED>The COB Recessed Range Die cast

11135L/W/C



35W Recessed COB LED downlight, IP20. Ideal for shops.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Physical Specification


08 Downlights Adjustable LED	
The COB Recessed Range Die cast	
11135L/W/C	
White	
Die Cast	
Circular	
177mm	

Cutout Hole Diameter	145mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	35W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	900mA
Voltage	37V
Safety Class	
Power(Watts)	33,3W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Citizen

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	28,8-37,8W
Power Factor	0,9
Constant Current	Yes
900mA	32-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Philips
Illumination Data	
Illumination Data Colour Temperature	4000K
Colour Temperature Lumen Output	3050lm
Colour Temperature Lumen Output Light Efficiency	3050lm 87,14lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3050lm 87,14lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3050lm 87,14lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3050lm 87,14lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3050lm 87,14lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3050lm 87,14lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3050lm 87,14lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3050lm 87,14lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3050lm 87,14lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3050lm 87,14lm/W 80 45° 16,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3050lm 87,14lm/W 80 45° 16,5cm 16,5cm 23cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	3050lm 87,14lm/W 80 45° 16,5cm 16,5cm 23cm

3 Years

Energy Label



Warranty

Certification & Warranty		

Weee Directive Yes