

04 Recessed Spots Adjustable LED>The COB Recessed Cylinders

11207C/B/W



2x7W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89015A

Related items



89015AT

Physical Specification



Item Group

04 Recessed Spots Adjustable LED


Family	The COB Recessed Cylinders
Order Code	11207C/B/W
Colour	Black
Material	Die Cast
Shape	Rectangular
Length	168mm
Width	90mm
Height	85mm
Cutout Hole Diameter	2x83mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	10V
Safety Class	
Power(Watts)	2x7W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	2x550lm
Light Efficiency	78,57lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	17,5cm
Box Width	9,5cm
Box Height	10cm
Pcs/Carton	24
Barcode	5291889058403
HS Code	9405409900

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes