

Special Offers>Wall & Ceiling LED

12106L/W/W



7W COB LED cylinder, with a modern design, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Gallery



Physical Specification

Item Group	Special Offers
Family	Wall & Ceiling LED
Order Code	12106L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	89mm


Diameter	110mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Coor	Duilt In
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Power(Watts)	6,6W
IP Rating	IP20
Light Source	LED built in
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	7W
Power Factor	0,8
Constant Current	Yes
IP Rating	IP20
Safety Class	

Illumination Data		
Colour Temperature	3000K	
Lumen Output	560lm	
Light Efficiency	80lm/W	
CRI	80	
Beam Angle	35°	
Illumination Diagram		

Packing Info Box Weight 0,78Kg Pcs/Carton 12 Barcode 5291889032663 HS Code 9405409900

Energy Label



Warranty	2 Years
Weee Directive	Yes

Certification & Warranty