

14 Wall & Ceiling LED>The COB LED Indoor Cylinders Aluminium

12115LA/W/W



15W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
ES CE	118mm
	115mm —
Physical Specification	
Item Group	14 Wall & Ceiling LED

Family
Order Code
Colour

Material

Shape

Height

The COB LED Indoor Cylinders Aluminium

12115LA/W/W

White

Aluminium

Circular

115mm

Diameter	118mm
Surface Wall	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	42V
Power(Watts)	14,7W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Philips

Gear

Gear Type	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,5-14W
Power Factor	0,9

Constant Current	Yes
350mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	LIFUD


Illumination Data

Colour Temperature	3000K
Lumen Output	1300lm
Light Efficiency	86,67lm/W
CRI	80
Beam Angle	50°
Illumination Diagram	

Packing Info

Box Weight	0,5Kg
Pcs/Carton	36
Barcode	5291889044901
HS Code	9405409900

Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes