

14 Wall & Ceiling LED>The SMD Cylinders Aluminium

12125LD/W/W



25W SMD LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12125LD/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	145mm
Diameter	195mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

25W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

600mA

Voltage

40V

Power(Watts)

24W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Samsung

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz


Yes

Power(Watts)


14,1-25,2W

Power Factor

0,9

Constant Current	Yes
600mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	2050lm
Light Efficiency	82m/W
CRI	80
Beam Angle	90°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pcs/Carton	18
Barcode	5291889061007
HS Code	9405409900

Energy Label



Warranty

2 Years

Weee Directive

Yes
