

09 LED Strips & Profiles>24V Linkable Modules Aluminium

38002A/D



3W LED Linkable module, IP20.

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Accessories







38007A

Physical Specification

| Item Group | 09 LED Strips & Profiles |
|------------|--------------------------------|
| Family | 24V Linkable Modules Aluminium |
| Order Code | 38002A/D |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 200mm |

| Width | 12mm |
|----------------------------|------------------|
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Indoor | Yes |
| | |
| Electrical Characteristics | |
| | |
| Fitting | |
| Input Type | Constant Voltage |
| Input Voltage | 24V DC |
| Safety Class | |
| Power(Watts) | 3W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD |
| F Mark | F |
| | |
| Illumination Data | |
| Colour Temperature | 6000K |
| Lumen Output | 144lm |
| Light Efficiency | 48lm/W |
| Illumination Diagram | |
| | |
| | |
| Packing Info | |
| Pcs/Carton | 100 |
| Barcode | 5291889017028 |
| HS Code | 9405104090 |
| | |

| Warranty | 3 Years |
|----------------|---------|
| Weee Directive | Yes |

Certification & Warranty