




- IP65 slim LED fitting .
- Stainless steel clips and suspension included.
- Polycarbonate body and diffuser.
- Supplied with non-dimmable LED driver.
- Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



050084

Physical Specification

Item Group	21 Industrial & Floodlights
Family	The IP65 LED Slim Range PC
Order Code	38136LA/C
Colour	White
Material	PC
Diffuser Material	PC
Shape	Rectangular
Length	1260mm
Width	55mm
Height	37mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	36W
IP Rating	IP65
Light Source	LED built in
Dimmable	No

Cable Length	50cm
F Mark	

Fitting

Input Type	Constant Current
Power(Watts)	36W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	36W
Power Factor	0,9
Constant Current	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data

Colour Temperature	4000K
Lumen Output	3200lm
Light Efficiency	88,9lm/W
CRI	80

Beam Angle
Illumination Diagram


120°


Packing Info

Pcs/Carton
Barcode
HS Code

20
5291889051114
9405104090

Energy Label



Certification & Warranty

Warranty
Weee Directive

2 Years
Yes